
# **COOPER LIGHTING - METALUX®**

#### DIMENSIONS

.....



#### DESCRIPTION

The floating appearance of the Softside compliments any decor with full, low brightness illumination. The soft floating profile of the frameless diffuser provides an appearance that is in tune with today's residential and commercial environments. With a wide variety of modular shapes and sizes, there is a Decorative Softside fixture for virtually every space and decorating possibility. The fixtures add the right touch to the kitchen, den, living room, bathroom, office or recreation room.



**WTS SERIES** 

1-1/2' x 2', 1' x 4', 1-1/2' x 4', or 2' x 2' Decorative 2 or 4 Lamp

### MODULAR FLUORESCENT SOFTSIDE CLOUD

- Utilizes Dur-illume lens technology which eliminates breakage when using acrylic lens
- Dur-illume 2200 material is naturally resistant to color shifts when exposed to UV typical of fluorescent lamps (lens will not yellow).
- The new white clips eliminate existing shadows while reducing sharp edges and promoting safe handling.
- Equipped with energy saving ballasts/complies with federal energy efficiency standards
- Soft floating cloud appearance for full illumination
- Die formed steel housing/baked white finish
- Variety of modular shapes and sizes
- Lift and shift frame assembly for ease of service and re-lamping
- Tuff-r-Puff durable acrylic lens
- UL/CUL Listed. Suitable for damp locations.

CATALOG	NOMINAL	LAMP				
NUMBER	SIZE	TYPE	Α	В	С	D
WTS-417	1-1/2' x 2'	4F17	17" (432mm)	4-1/2" (114mm)	13-3/4" (349mm)	12-3/4" (324mm)
WTS-2U6T8	2' x 2'	2FU32	26" (624mm)	4-1/2" (114mm)	24-1/2" (622mm)	22-5/16" (567mm)
WTS-232	1' x 4'	2F32	11-1/2" (292mm)	4-1/2" (114mm)	8-1/4" (210mm)	7-1/4" (184mm)
WTS-432	1-1/2' x 4'	4F32	17" (432mm)	4-1/2" (114mm)	13-3/4" (349mm)	12-3/4" (324mm)

## ORDERING INFORMATION

BIORGIBIAI

SAMPLE NUMBER: WTS-432-D-W-120V-EB81-U Diffuser/Lens Options **Packaging** Series **D**=Dropped (See Options Section) Softside U=Unit Pack Ballast Type (1) WTS=Series Blank=Standard Magnetic Ballast Frame Finish (20W only) W=White Number LE3=T12 Magnetic Energy Saving EB8\_= T8 Electronic Instant Start.

of Lamps 2 or 4 lamps (Not Included)

Wattage (Length) 20=20W T12 (24")(3) 17=17W T8 (24")(3) U6=40W T12 (24") **U6T8**=31W T8 (24") 40=40W T12 (48") 32=32W T8 (48")

LTS=Low Trigger Start (20 Watt only (120V only) HTS=High Trigger Start (20 Watt only) Voltage (1)

**120V**=120 Volt 277V=277 Volt 347V=347 Volt UNV=Universal Voltage 120-277 (2)

Starting Type

Options GL=Single Element Fuse **GM**=Double Element Fuse

Emergency - for EM installed, see EM options table (4)

Total Harmonic Distortion < 10% No. of Ballast 1, 2 or 3 EB8\_/PLUS= T8 Electronic Instant Start. High Ballast Factor >1.13. Total No. of Harmonic Distortion < 20% Ballast 1, 2 or 3

ER8\_= T8 Electronic Program Rapid Start. Total Harmonic Distortion < 10% No. of Ballast

1, 2 or 3

EB2\_=T12 Electronic Rapid Start.

No. of Ballast 1 or 2

(For complete details on generic or to specify manufacturer's ballast see pg. 469)

NOTES: <sup>(1)</sup>Products also available in non-US voltages and frequencies for international markets. <sup>(2)</sup>Not available when specifying emergencies, voltage must be specific. <sup>(3)</sup>Outboard socket position standard on 2-lamp. <sup>(4)</sup>Not available for 2' version.